Ceramic cutting-off wheel

K 960 TX *SPECIAL*

Fe·S·Cl <0,1%

Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Ceramic Al. oxide
Bond	■■■■■■■
Aggression	■■■■■■■
Service life	■■■■■■■

Materials

Steel	●
Stainless steel	●
High alloy steel	●
Carbon steel	●
Titanium	●

Product benefit

Free of iron, sulfur and chlorine - Outstanding performance in daily use - Highest cutting performance, even with low grinding pressure - 10 pieces in a tin with viewing window for easy removal

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1 x 22,23	▬▬	80 m/s	13300 rpm	50	362590
125 x 1 x 22,23	▬▬	80 m/s	12200 rpm	50	362589

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de